

EZ Zone[®] Tape

PURGE GAS RETAINING TAPE

US & FOREIGN PATENTS PENDING

FOR CLEAN CONTAMINANT-FREE WELDING



**HIGH HEAT
RESISTANT**

FEATURES

Adhesive Free Zone

- Weld Joint Free from Adhesive, Creating a Superior Weld


High Quality & Safe Components

- Halogen & Chlorofluorocarbon Free
- Improves the Safety of Your Work Environment
- 3 mil (75 micron) Foil Adheres and Conforms to Irregular Surfaces

High Heat Temperature Resistant

- Adhesive Portion of Aluminum Tape Withstands Temperatures Up to 500°F (260°C)

SIMPLY SEAL THE ROOT GAP



1 ALIGN

- Place Adhesive Free Zone Over Root Gap
- Adhesive Edges Hold Tape in Place



2 INTRODUCE GAS

- Insert Purge Gas Needle Into Root Gap
- Introduce Gas
- Evacuate O₂
- Commence Welding



The All Purpose Solution

- For Conventional Uses in the Field such as Heating, Air Conditioning, Refrigeration and Acting as a Vapor Barrier
- Capping Pipe Ends During Transport
- Controls Release of Gas by Sealing Root Gap

High Heat Temperature Resistant

- Aluminum Coated Adhesive Withstands Temperatures up to 500°F (260°C)





High Quality & Safe Components

- Halogen and Chlorofluorocarbon Free

PROMOTES
SAFETY
IN THE
WORKPLACE

SPECIFICATIONS FOR ALUMINUM WELDING TAPE


EZ Tape® Types and Sizes

PRODUCT	ITEM NO.	DESCRIPTION	WIDTH		ADHESIVE FREE "ZONE" WIDTH		LENGTH		CASE QUANTITY
			ENGLISH	METRIC	ENGLISH	METRIC	ENGLISH	METRIC	
	EZ-ZT 2.5	EZ Zone® Tape	2.5"	64 mm	1"	25 mm	75'	23 m	18 Rolls
	EZ-ZT 4.0	EZ Zone® Tape	4.0"	102 mm	2"	51 mm	75'	23 m	12 Rolls
	EZ-T 1.0	EZ Tape® Fully-coated	1.0"	25 mm	N/A		75'	23 m	48 Rolls
	EZ-T 2.0	EZ Tape® Fully-coated	2.0"	51 mm	N/A		75'	23 m	24 Rolls

▶ Heat Resistance:	Adhesive	500°F	260°C
	Aluminum Foil	1100°F	593°C
▶ Minimum Application Temperature		10°F	-12.5°C

For additional product information,
quotations and ordering, please contact:

Distributed By:



Aquasol Corporation

80 Thompson Street
N. Tonawanda, NY 14120 USA

Toll Free: 1.800.564.WELD (9353)
Phone: 716.564.8888
Fax: 716.564.8889

Email: info@aquasolcorporation.com
aquasolwelding.com



American Welding Society
Sustaining Company Member



MADE IN THE USA